



AMSN CF & PF NAVY CLOTH FACING

DESCRIPTION

AMSN CF Navy cloth facing is a 100% woven fiberglass cloth that is resin treated to ensure durability and non flammability. The cloth conforms to USCG 164.109 (non combustibility) and 164.112 (interior finish) and Military Specification MIL-C-20079 Type 1, Class 2.

APPLICATION

AMSN CF is used primarily as a facing material for marine insulation boards such as polyimide (DOD-I-24688 Type 2, Class 1), fiberglass (MIL-I-742 Type 1) and mineral wool. AMSN CF can be perforated (AMSN PF) to meet the requirements of Military Spec. MIL-A-23054 and DOD-I-24688 Type 2, Class 2 for acoustic marine insulation applications.

PHYSICAL DATA

BASE FABRIC	4 Harness Satin
FINISHED WEIGHT	13.50 oz/sy
THICKNESS	.0134"
TENSILE STRENGTH	510 x 380
CONSTRUCTION	48 x 32
AVAILABLE WIDTHS	24, 48, 72"
STD ROLL LENGTHS	250 ly

Disclaimer: This information contained herein is believed to be accurate and correct. However, no warranty, implied or expressed, is made, regarding its accuracy or the results to be obtained from the use of this information.