



AMSN SEWING THREADS

AMSN 753

This is a machine sewing thread made from 100% fiberglass yarns that are uniformly coated with Teflon. R-753 threads are fully sintered, made with a left hand twist and conform to MIL-C-20079 TY3, CL3. It is available in 3 diameters and a 2 lb spool put up.

AMSN1330

This thread is designed to be either a hand or a machine sewing thread. It is made from 100% fiberglass yarns and is uniformly coated with Teflon for ease in processing. 1330-167 conforms to MIL-C-20079 TY3, CL4.

AMSN 40FS

This thread is manufactured from 100% fiberglass yarns that are plied with stainless steel wires, then coated with Teflon to form a hand sewing thread with superior strength. MAS-40FS is a unsintered.

AMSN 50NS

This thread is made from 100% aramid yarns plied with stainless steel wires. It has been designed for hand sewing operations and provides superior strength and performance at elevated temperatures.

	753-12	753-18	753-24	30	40FS	50NS
Diameter	.015"	.018"	.021"	.027"	.041"	.051"
Tensile Strength	13 lb/in.	20 lb/in.	25 lb/in.	55 lb/in.	60 lb/in.	20 lb/in.
Yards per lb.	3200	2150	1600	1150	340	750
Fiber	FG	FG	FG	FG	FG	Aramid
Reinforcement	None	None	None	None	304SS	304SS
Coating	PTFE	PTFE	PTFE	PTFE	PTFE	None
Spool Size	2 lb.	2 lb.	2 lb.	1/2, 2 lb.	1/2, 2 lb.	2 lb.

Disclaimer: This information contained herein is believed to be accurate and correct. However, no warranty, implied or expressed, is made, regarding its accuracy or the results to be obtained from the use of this information.